



## ***Knauf Baseboard***

Knauf Baseboard is a handy-sized plasterboard suitable for use as a base for plastering. Made from aerated gypsum core, with premium paper liners on either side. Ideally suited to receive a plaster, ready mixed finish or for direct decoration.

*Product-Data-Sheet*

***Build on us.***



### **Areas of Application**

Suitable for patching and repair jobs. Baseboard is not suitable for high humidity areas.

### **Compliance Standards**

EN520 Type P

### **Key Benefits**

- Strong and versatile
- Standard square edge
- Fully recyclable
- Quick and easy to install
- Multiple layers can be used for added performance
- Provides a smooth surface ready for finishing

Creation Date: 24/10/2023  
Revision Reference: 004  
Revision Date: 31/03/2024

Performance Data

Thickness (mm)	Reaction to Fire (R2F)	Thermal Conductivity ( $\lambda$ ) (W/mK)	Water Vapour Resistance ( $\mu$ ) (Dry/Wet) (EN 12524)	Board Density (kg/m <sup>3</sup> )
9.5	A2-s1, d0	0.25	10/4	642

Technical Information

Thickness (mm)	Width (mm)	Length (mm)	Edge Type	Colour	Weight (kg/m <sup>2</sup> )	Taper Width (mm) (Max/Min)	Taper Depth (mm) (Max/Min)	Number of Tapered Edges	Material Number
9.5	900	1220	Square	Ivory	6.1	0	0	0	243477

## Sustainability

### Recycled Content

12.64%

2024 average by mass for all UK produced plasterboards, recycled gypsum & paper.

### Recyclability

This product should be recycled separately to non-plasterboard waste. Please ensure it has no or minimal contamination from non-gypsum based materials, as this will affect its recyclability.

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

## Storage and Handling

Product must be stored flat and on a surface strong enough to support them. Keep boards dry at all times.

Refer to the HSE Manual Handling Operations Regulation for best practice guidance.

## Packaging

Product is stacked on recycled chipboard bearers and can be recycled with wood waste.

Pallet wrap is made from 30% recycled plastic content.

## Service Life

Service life of this product is 60 years and/or the lifetime of the building.

## Disposal

Disposal should be in accordance with local authority requirements. Keep gypsum based products in their own recycling area to minimise contamination from non-gypsum based products. European Waste Catalogue code: 17 08 02

## Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

## Application / Installation

Typically used as a patch and repair product or can be installed as part of a partition system, wall lining and ceiling system with Knauf fixings, jointing, taping and finishing products.

Use Knauf plasterboard screws at a distance of 300mm apart on horizontal joints and 10mm from bound edge and 13 mm from unbound edges in from the edge of the board.

Tape and Joint using Knauf's system tapes and jointing compounds.

Boards can be taped and jointed using Knauf Jointing Products, we recommend the use of a wallboard primer when finishing the board directly with paint.

The type and number of layers of board used will influence the structural, fire, acoustic and thermal performance of the system.

All products must be installed in accordance with Knauf's recommendations and the current recommendations of BS 8000-8 2023.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

## Certification

[Environmental Product Declaration](#)

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 24/10/2023  
Revision Reference: 004  
Revision Date: 31/03/2024