



## ***Knauf Sound Panel***

Knauf Sound Panel offers enhanced levels of sound performance and a greater density, making it ideal for residential applications or where a minimum of 10kg/m<sup>2</sup> is required. Ideal for use in conjunction with robust details.

Sound Panel is made from an aerated gypsum core, with premium paper liners on either side. Can be finished with Knauf Jointing Products and Knauf Ready mix spray finish before decoration.

*Product-Data-Sheet*

***Build on us.***

### **Areas of Application**

Suitable for partitions and linings where an increased level of acoustic performance may be required.

Sound Panel is not suitable for areas of high humidity.

### **Compliance Standards**

EN520 A & D

### **Key Benefits**

- Strong and versatile
- Enhanced levels of sound performance
- Tapered edge
- Fully recyclable
- Quick and easy to install
- Multiple layers can be used for added performance
- Provides a smooth surface ready for finishing

Creation Date: 11/08/2023  
Revision Reference: 004  
Revision Date: 01/04/2025

**Product Information****Performance Data**

Thickness (mm)	Reaction to Fire (R2F)	Thermal Conductivity ( $\lambda$ ) (W/mK)	Water Vapour Resistance ( $\mu$ ) (Dry/Wet) (EN12524)	Board Density (kg/m <sup>3</sup> )
12.5	A2-s1, d0 (B)	0.25	10/4	800

**Technical Information****Tapered Edge**

Thickness (mm)	Width (mm)	Length (mm)	Colour	Weight (kg/m <sup>2</sup> )	Taper Width (mm) (Max/Min)	Taper Depth (mm) (Max/Min)	Number of Tapered Edges	Material Number
12.5	1200	2400	Blue	10	80/40	2.5/0.6	2	404632
	1200	2700	Blue	10	80/40	2.5/0.6	2	414141

## Sustainability

### Recycled Content

12.64%

2024 average by mass for all UK produced plasterboards, recycled gypsum & paper.

### Recyclability

This product should be recycled separately to non-plasterboard waste. Please ensure it has no or minimal contamination from non-gypsum based materials, as this will affect its recyclability.

### Storage and Handling

Product must be stored flat and on a surface strong enough to support them. Keep boards dry at all times. Refer to the HSE Manual Handling Operations Regulation for best practice guidance.

### Packaging

Product is stacked on recycled chipboard bearers and can be recycled with wood waste.

Pallet wrap is made from 30% recycled plastic content.

### Service Life

Service life of this product is 60 years and/or the lifetime of the building.

### Disposal

Disposal should be in accordance with local authority requirements. Keep gypsum based products in their own recycling area to minimise contamination from non-gypsum based products. European Waste Catalogue code: 17 08 02

## Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

## Application / Installation

Typically installed as a part of a partition system, wall lining and ceiling system with Knauf fixings, jointing, taping and finishing products.

Use Knauf plasterboard screws at a distance of 300mm on horizontal joints and 10mm from bound edge and 13mm from unbound edges in from the edge of the board.

Knauf Jointing Compounds with Knauf Paper Joint Tape can be used to finish the joints followed by Knauf Wallboard Primer prior to decoration. Knauf Ready Mix Airless Finishes (RMF), can be spray applied to the board following the jointing process. No Wallboard Primer would be required if using RMF to finish.

Should an alternative Gypsum or surface finish be required, seek guidance from the supplier on application.

The type and number of layers of board used will influence the structural, fire, acoustic and thermal performance of the system.

All products must be installed in accordance with Knauf's recommendations and the current recommendations of BS 8000-8 2023.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

## Certification

[Environmental Product Declaration](#)

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 11/08/2023  
Revision Reference: 004  
Revision Date: 01/04/2025